# Aluminum Adjustable Height Gantry Crane with Total Locking Phenolic Casters 15 Ft. Wide x 12 Ft. Max Usable Height 6,000 Lb. Capacity Silver

**MODEL AHA-6-15-12-TLC**

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes with Total Locking Casters



## PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines lightweight and rigid, sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. The lightweight I-beam allows simple height adjustments. All pinned connections make it possible for single person set up and take down in just minutes. Included are two straps, allowing one person to transport the gantry crane in one neat package. Unit comes standard with total locking casters.

## KEY FEATURES

- Heavy-duty welded aluminum construction for long lasting use
- Easy adjustable height can be done with fork truck or other overhead lifting device
- Beam length allows for use with items, both large and small
- All units comply with applicable CMAA and ANSI specifications

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**588 lbs** | ASSEMBLED SIZE<br>**64.6875" W x 180" L x 156" H** | SHIP WEIGHT<br>**610 lbs** |
| PACKAGE 1 SIZE<br>**64" W x 64" D x 20" H** | COLOR / FINISH<br>**Silver** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS



## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 6,000 |
| **Adjustable Clearance Range (in.)** | 122 to 146 |
| **Beam Height (in.)** | 12 |
| **Overall Beam Length (in.)** | 180 |
| **Usable Beam Length (in.)** | 156-1/4 |
| **Flange Width (in.)** | 7 |
| **Increment Height Adjustment (in.)** | 6 |
| **Caster Qty/Diameter/Width (in.)** | (4) 8 x 3 |
| **Caster Material** | Phenolic |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=1756