

Galvanized Alternate Tread Stair 68 Degrees 78-3/8 In. x 23-1/2 In. x 209-7/8 In. 350 Lb. Capacity Silver

MODEL ATS-14-68-HDG

Industrial Ladders / Alternating-Tread Stairs



PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

KEY FEATURES

- Two-sided hand railing provides added user safety
- Steps are constructed of a raised steel surface providing better traction
- Handrails have a safety yellow powder coat finish
- Steel steps and platform have a durable hot dip galvanize finish

CORE PRODUCT DATA

ASSEMBLED WEIGHT
350 lbs

ASSEMBLED SIZE
209.875" W x 78.375" L x 23.5" H

SHIP WEIGHT
610 lbs

PACKAGE 1 SIZE
29" W x 188" D x 17" H

COLOR / FINISH
Silver

FREIGHT TYPE
LTL Palletized

AVAILABILITY Quote Required - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	350
Number of Steps	24
Top Step Height (in.)	168
Step Angle (degrees)	68
Safety Chain (in.)	3/16
Top Step Depth (in.)	9-3/4
Top Step Width (in.)	23-5/8
Step (excluding top step) Depth (in.)	10-1/2
Step (excluding top step) Width (in.)	9-1/8
Step Height Spacing (in.)	7
Handrail Height (in.)	12-1/4
OSHA	29 CFR 1910.25(e`)

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=612>