

# Galvanized Alternate Tread Stair 68 Degrees 54-1/8 In. x 23-1/2 In. x 149-5/8 In. 350 Lb. Capacity Silver

**MODEL ATS-9-68-HDG**

Industrial Ladders / Alternating-Tread Stairs



## PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

## KEY FEATURES

- Two-sided hand railing provides added user safety
- Steps are constructed of a raised steel surface providing better traction
- Handrails have a safety yellow powder coat finish
- Steel steps and platform have a durable hot dip galvanize finish

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**212 lbs**

**ASSEMBLED SIZE**  
**149.625" W x 54.125" L x 23.5" H**

**SHIP WEIGHT**  
**256 lbs**

**PACKAGE 1 SIZE**  
**30" W x 144" D x 17" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Quote Required - Please Contact Sales

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                       |                    |
|---------------------------------------|--------------------|
| Uniform Capacity (lb.)                | 350                |
| Number of Steps                       | 15                 |
| Top Step Height (in.)                 | 107-3/4            |
| Step Angle (degrees)                  | 68                 |
| Safety Chain (in.)                    | 3/16               |
| Top Step Depth (in.)                  | 9-3/4              |
| Top Step Width (in.)                  | 23-5/8             |
| Step (excluding top step) Depth (in.) | 10-1/2             |
| Step (excluding top step) Width (in.) | 9-1/8              |
| Step Height Spacing (in.)             | 7-3/16             |
| Handrail Height (in.)                 | 12-1/4             |
| OSHA                                  | 29 CFR 1910.25(e`) |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=612>