

Vinyl Dock Seal 19 In. 8 Ft. x 8 Ft. Black

MODEL D-150-19

Loading Dock Equipment / Dock Seals

PRODUCT OVERVIEW

The superior nylon reinforced vinyl facing has a higher tear strength than equivalent weight hypalon. The chemically sealed ends prevent moisture infiltration. It is mounted and bonded on a durable pressure treated wood and contains a full height air escape tunnel. The unit consists of a three (3) piece construction with beveled fronts and a through the wall installation kit that is included. Five inch (5") maximum compression is recommended. Application with a flush dock to building in conjunction with an Edge-O-Dock use a twenty (20) inch projection Dock Seal. To ensure proper size complete the survey sheet. This unit is non-returnable.

KEY FEATURES

- Three foam-filled pads offer full dock protection
- Maximum compression design offers the maximum protection
- Built-in air tunnels allow air to escape when contacted by a trailer
- Mounting hardware and installation instructions make installation quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
137 lbs

ASSEMBLED SIZE
108" W x 19" L x 120" H

SHIP WEIGHT
251 lbs

PACKAGE 1 SIZE
36" W x 120" D x 25" H

COLOR / FINISH
Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

PRODUCT SPECIFICATIONS

Projection (in.)	19
Nylon Reinforced Vinyl (oz.)	36
Nylon Reinforced Guide Strips (in.)	2
Top Height (in.)	12
Side Wall Width (in.)	9-1/2
Face Width (in.)	12
Maximum Compression (in.)	5
Standard Guide Stipe Height (in.)	30
Side Height (in.)	96
Max Door Width (in.)	96
Max Door Height (in.)	96

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=19>