

Steel Electric Powered Tugger 1000 Lb. Pull Capacity Yellow/Black

MODEL E-TUG-10

Industrial Carts & Dollies / Electric Powered Tuggers



PRODUCT OVERVIEW

The electric powered Tuggers are ideal for industrial facilities, hospitals, airports, and wholesale/retail stores. The unit is designed of a durable construction for constantly strong use on a daily basis. Tugger is perfect for confined areas due to its short turning radius. An infinite throttle position allows for unlimited forward and reverse adjustments for precise positioning. Unit can be tilted forward manually to align the hitch if needed. An integral battery charger and level gauge allow for convenient as needed charging and level awareness. Pin hitch standard, optional attachments available.

KEY FEATURES

- Ergonomic handle for easy operation while diminishing the need of bending and twisting
- Dead-man activation for the utmost safety and security
- Forward and reverse operations for precise maneuverability
- High torque for heavy duty operations

CORE PRODUCT DATA

ASSEMBLED WEIGHT
200 lbs

ASSEMBLED SIZE
50.375" W x 31.75" L x 20.25" H

SHIP WEIGHT
258 lbs

PACKAGE 1 SIZE
42" W x 49" D x 57" H

COLOR / FINISH
Yellow & Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Pull Capacity (lb.)	1,000
Drive Motor	24V DC
Battery Qty./Volts	(2) 12V
Horsepower (HP)	0.5
Handle Height (in.)	50-3/8
Charging Amperage Required	20
Charger Voltage	120V
Front Wheel Qty./Size (in.)	(2) 10-1/4 x 3-3/4
Front Wheel Material	Solid Foam
Rear Caster Qty./Size (in.)	(2) 3 x 1-1/2
Rear Caster Material	Rubber
Loaded Speed (MPH)	2.3
Unloaded Speed (MPH)	2.7
Pulling Force (lbs.)	56
Pull Motor (KW)	0.4
Maximum Gradeability (degrees)	2
Unloaded Gradeability (degrees)	3
Battery Depth	7.76
Battery Width	5.125
Battery Height	7.125
Battery Weight	21.67
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	Batteries or Cells, Offered for transportation as a Hazard Class 4, 8 or 9
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1019>