

Steel Ground Lift Scissor Table 44 In. x 84 In. 3000 Lb. Capacity Blue

MODEL EHLTG-4484-3-54

Ergonomic Solutions / Ground Lift Scissor Tables with Handrails

PRODUCT OVERVIEW

The ground lift scissor table is designed for use when fork trucks are not available. The pallets can be loaded onto the platform with pallet trucks and raised to an ergonomic working height. Safety features include an entry-side electric toe guard to protect pinch points during lowering of the table, velocity fuse to maintain platform height in the event of a hose or fitting failure, foot control, maintenance prop, and upper travel limit switch to stop the table at maximum height and reduce motor wear. The motor is totally enclosed standard with additional voltage options available. The remote power unit can be located up to eight (8) feet away from the table. Optional accordion skirting is available.

KEY FEATURES

- Pallets can be loaded onto the platform and raised to a working height
- Features toe guard to protect pinch points
- Guardrails for stability and support
- Remote power unit can be located up to eight feet away from the table

CORE PRODUCT DATA

ASSEMBLED WEIGHT
2556 lbs

ASSEMBLED SIZE
54" W x 92" L x 70.6875" H

SHIP WEIGHT
2889 lbs

PACKAGE 1 SIZE
72" W x 98" D x 61" H

COLOR / FINISH
Blue / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Power Source	Electric - Corded
Maximum Height (in)	54
Minimum Height (in)	0.5
Maximum Travel Distance (in)	53.5
Operation Method	Foot Operated
Overload Protection	Yes
Lifting Speed (sec/ft)	32
Horsepower (hp)	2
Phase	Three Phase
Voltage (V)	460
Power Cord Length (ft)	8
Installation Hardware Included	Not Required

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1632>