Steel Electric Powered Low Profile Floor Crane 1600 Lb. Capacity Yellow

MODEL EPFC-16-LP

Overhead Lifting / Electric Powered Floor Cranes



PRODUCT OVERVIEW

The low profile electric powered floor crane is a safe and efficient way to lift and move equipment. With the push of a button, the unit raises and lowers loads. Its low profile design can be maneuvered in narrow and crowded warehouses. An included swivel hook with safety latch provides security during lifting. Poly-on-steel, steer and load wheels provide a smooth roll. The handle is both ergonomic and functional, featuring a throttle with infinite forward and reverse speed adjustments. Emergency reverse belly switch instantly reverses direction. Horn is also included.

KEY FEATURES

- Electromagnetic disc brake
- Walk behind design
- 24V internal battery
- Battery level gauge and charger included

CORE PRODUCT DATA

ASSEMBLED WEIGHT **950 lbs**	ASSEMBLED SIZE **30.125" W x 65.375" L x 75" H**	SHIP WEIGHT **1064 lbs**
PACKAGE 1 SIZE **44" W x 86" D x 82" H**	COLOR / FINISH **Yellow**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS






PRODUCT SPECIFICATIONS

Uniform Capacity (lbs.)	1,600
Arm Height (in.)	70
Drive Motor	DC24V
Battery Type	Acid
Controls	Hand
Swivel Caster QTY	1
Swivel Caster Diameter (in.)	10
Swivel Caster Width (in.)	3-1/8
Rigid Caster QTY	2
Rigid Caster Diameter (in.)	3-1/8
Rigid Caster Width (in.)	3
Caster Material	Poly on Steel
Caster Color	Red
Handle Height (in.)	50
Handle Diameter (in.)	1-1/2
Handle Type	Drive
Raised Arm Height (in.)	109-1/2
Overall Height (in.)	75
Overall Width (in.)	30-1/8
Overall Length (in.)	65-3/8
Lift Speed w/o Load (sec.)	0.70
Lift Speed w/Load (sec.)	0.50
Lower Down Speed w/o Load (sec.)	0.75
Lower Down Speed w/Load (sec.)	1
Travel Speed w/o Load (m/h)	2.7
Travel Speed w/Load (m/h)	1.8
Gradeability (pct.)	0%
Battery Depth	11

1 additional technical attributes are available on the live Vestil product page.

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA