

Steel Electric Pallet Truck with AGM Batteries 27 In. x 48 In. 4500 Lb. Capacity

MODEL EPT-2748-45-AGM

Ergonomic Solutions / Fully Powered Electric Pallet Trucks

PRODUCT OVERVIEW

The fully powered electric pallet truck has an easy and quick operation. The unit raises and lowers loads with a push of a button. It can maneuver loads in warehouses and trailers. The reinforced welded forks have adjustable tie-rods that provide long service. The high-torque DC drive and lift motors handle heavy-duty jobs. Unit includes integral battery charger, battery level gauge, and emergency battery disconnect. The truck rolls smoothly on poly-on-steel, steer and load wheels. Ergonomic handle features easy to operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuate...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1036 lbs
ASSEMBLED SIZE
52" W x 76" L x 30.25" H
SHIP WEIGHT
992 lbs
PACKAGE 1 SIZE
42" W x 85" D x 57" H
COLOR / FINISH
Black / Yellow
FREIGHT TYPE
LTL Palletized
AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Overall Fork Width (in.)	27
Overall Fork Length (in.)	48
Uniform Capacity (lb.)	4500
Lowered Height (in.)	3.2
Raised Height (in.)	8.2
Battery Type	(4) AGM
DC Motor Voltage	24
Battery Charger	120V Input, 24V/20 amp
Turn Radius (in.)	69
Drive KW	1.2
Lift Motor KW	2.0
Operation at Full Charge (hours)	6 to 7
Operation When Used Intermittently (hours)	8
Drive Wheel Diameter (in.)	10
Drive Wheel Width (in)	3-1/8
Load Roller Diameter (in.)	2-3/4
Load Roller Width (in.)	3
Stabilizing Roller Diameter (in.)	1-1/2
Stabilizing Roller Width (in.)	3
Wheel & Roller Type	Poly on Steel
Battery Depth	10
Battery Width	28
Battery Height	9
Battery Weight	120
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=342>