# Steel Electric Pallet Truck with AGM Batteries and Rider Platform 27 In. x 48 In. 4500 Lb. Capacity

**MODEL EPT-2748-45-RP-AGM**

Ergonomic Solutions / Fully Powered Electric Pallet Trucks



## PRODUCT OVERVIEW

The fully powered electric pallet truck has an easy and quick operation. The unit raises and lowers loads with a push of a button. It can maneuver loads in warehouses and trailers. The reinforced welded forks have adjustable tie-rods that provide long service. The high-torque DC drive and lift motors handle heavy-duty jobs. Unit includes integral battery charger, battery level gauge, and emergency battery disconnect. The truck rolls smoothly on poly-on-steel, steer and load wheels. Ergonomic handle features easy to operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuate...

## KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**1056 lbs** | ASSEMBLED SIZE<br>**30" W x 80.75" L x 51" H** | SHIP WEIGHT<br>**1076 lbs** |
| PACKAGE 1 SIZE<br>**42" W x 85" D x 57" H** | COLOR / FINISH<br>**Black / Yellow** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Overall Fork Width (in.)** | 27 |
| **Overall Fork Length (in.)** | 48 |
| **Uniform Capacity (lb.)** | 4500 |
| **Lowered Height (in.)** | 3.4 |
| **Raised Height (in.)** | 7.8 |
| **Battery Type** | (4) AGM |
| **DC Motor Voltage** | 24 |
| **Battery Charger** | 120V Input, 24V/20 amp |
| **Turn Radius (in.)** | 78-3/8 |
| **Drive KW** | 1.2 |
| **Lift Motor KW** | 2.0 |
| **Operation at Full Charge (hours)** | 6 to 7 |
| **Operation When Used Intermittently (hours)** | 8 |
| **Drive Wheel Diameter (in.)** | 10 |
| **Drive Wheel Width (in)** | 3-1/8 |
| **Load Roller Diameter (in.)** | 2-3/4 |
| **Load Roller Width (in.)** | 3 |
| **Stabilizing Roller Diameter (in.)** | 1-1/2 |
| **Stabilizing Roller Width (in.)** | 3 |
| **Wheel & Roller Type** | Poly on Steel |
| **Battery Depth** | 10 |
| **Battery Width** | 28 |
| **Battery Height** | 9 |
| **Battery Weight** | 120 |
| **Battery Freight Class** | 60 |
| **Battery NMFC Number** | 60700 |
| **Battery NMFC Description** | Gel batteries on unit |
| **Lithium Battery Configuration** | C -- Contained In |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=342