

Steel Floor Lock 4-5/8 to 5-3/4 In. Height Silver

MODEL FL-LKH-4

Facilities Maintenance / Polyurethane Floor Locks

PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to create a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

CORE PRODUCT DATA

ASSEMBLED WEIGHT 4 lbs	ASSEMBLED SIZE 4.625" W x 7.625" L x 4.5" H	SHIP WEIGHT 4 lbs
PACKAGE 1 SIZE 5" W x 8" D x 5" H	COLOR / FINISH Silver	FREIGHT TYPE Parcel
AVAILABILITY Available Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.		QUICKSHIP: YES

PRODUCT SPECIFICATIONS

Lowered Height (in.)	4-5/8
Raised Height (in.)	5-3/4
Foot Pad Diameter (in.)	2-9/16
Foot Pad Material	Thermoplastic polyurethane (TPU)
Grip Pedal Material	Thermoplastic polyurethane (TPU)
Mounting Plate (in.)	3-15/16 x 4-1/2
Slotted Holes on Center (in.)	3-1/16, 3-11/16
Mounting Plate Thickness (in.)	3/16
Slotted Mounting Hole Width/Height (in.)	3/8 x 13/16
Inside Bolt Hole Spacing (in.)	2-9/16 X 3-3/16
Outside Bolt Hole Spacing (in.)	3-3/16 X 3-11/16
Suggested Caster Size (in.)	4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1067>