# Steel Floor Lock 4-5/8 to 5-3/4 In. Height Silver

**MODEL FL-LKH-4**

Facilities Maintenance / Polyurethane Floor Locks



## PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to created a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

## KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

## CORE PRODUCT DATA


| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**4 lbs** | ASSEMBLED SIZE<br>**4.5" W x 7.625" L x 4.625" H** | SHIP WEIGHT<br>**4 lbs** |
| PACKAGE 1 SIZE<br>**5" W x 8" D x 5" H** | COLOR / FINISH<br>**Silver** | FREIGHT TYPE<br>**Parcel** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**ADDITIONAL PRODUCT VIEWS**





## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Lowered Height (in.)** | 4-5/8 |
| **Raised Height (in.)** | 5-3/4 |
| **Foot Pad Diameter (in.)** | 2-9/16 |
| **Foot Pad Material** | Thermoplastic polyurethane (TPU) |
| **Grip Pedal Material** | Thermoplastic polyurethane (TPU) |
| **Mounting Plate (in.)** | 3-15/16 x 4-1/2 |
| **Slotted Holes on Center (in.)** | 3-1/16, 3-11/16 |
| **Mounting Plate Thickness (in.)** | 3/16 |
| **Slotted Mounting Hole Width/Height (in.)** | 3/8 x 13/16 |
| **Inside Bolt Hole Spacing (in.)** | 2-9/16 X 3-3/16 |
| **Outside Bolt Hole Spacing (in.)** | 3-3/16 X 3-11/16 |
| **Suggested Caster Size (in.)** | 4 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **30 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=1067