

Steel Maintenance Ladder 58 Degree 10 Perforated 24 In. Step Width 350 Lb. Capacity Yellow

MODEL LAD-MM-10-P-YL

Industrial Ladders / Maintenance Ladders



PRODUCT OVERVIEW

Portable maintenance ladder for use around a variety of stores and inventory rooms. Constructed of square tubing framework, which handles uniform capacities up to 350 lbs. hand railing provides user safety while ascending or descending the unit. Distance between steps is 10". Powder coated finish for baked in added toughness.

KEY FEATURES

- Complies with ANSI 14.7 and OSHA 1910.29 specifications
- Portable ladder allows workers to easily maneuver throughout the warehouse
- Simple tilt back design allows for easy portability
- Removable access chain increases worker safety when not in use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
202 lbs

ASSEMBLED SIZE
130" W x 81.125" L x 32" H

SHIP WEIGHT
310 lbs

PACKAGE 1 SIZE
40" W x 132" D x 26" H

COLOR / FINISH
yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	350
Step Angle (degrees)	58
Step (qty.)	10
Top Step Height (in.)	100
Hand Rail Height (in.)	30
Top Platform Length (in.)	21
Top Platform Width (in.)	24
Safety Chain (in.)	3/16
Step Width (in.)	24
Step Depth (in.)	7
Step Spacing (in.)	10
Wheel Quantity/Diameter/Width (in.)	(2) 4 x 1-1/4
Wheel Type	Poly-on-Poly
Step Style	Perforated
OSHA	1910.29
ANSI	A14.7

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=608>