

Steel Lite Load Lift With Foot Pump, Fixed Wheels and Wheel Lock 20 In. x 20 In. Platform 400 Lb. Capacity Blue

MODEL LLH-202053-FWWL

Ergonomic Solutions / Lite Load Lifts



PRODUCT OVERVIEW

The Lite load lift is ideal for lifting and transporting loads from delivery trucks to docks, or use to inventory storage systems. Easy to operate with foot pump and a steel construction. The unit rolls smoothly on poly-on-poly rear wheels, four swivel front casters and a hand operated floor lock. Located on the handle are two (2) rollers to ease loading into delivery trucks. Unit also includes a wheel lock for steadiness when not in motion.

KEY FEATURES

- Solid steel construction provides long lasting rugged use
- Easy to operate lift system makes lifting products to ergonomic heights simple
- Wheel lock capabilities for stability and control
- Two rollers on handle provide easy unit loading into delivery trucks

CORE PRODUCT DATA

ASSEMBLED WEIGHT
178 lbs

ASSEMBLED SIZE
66" W x 29.75" L x 20.0625" H

SHIP WEIGHT
180 lbs

PACKAGE 1 SIZE
41" W x 49" D x 71" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	400
Platform Width (in.)	20
Platform Length (in.)	20
Lowered Height (in.)	3-1/8
Raised Height (in.)	51-1/8
Lift per Foot Pump (in.)	1
Horizontal Load Center (in.)	10
Operation Type	Manual - Foot Pump
Rear Wheel Qty./Diameter/Width (in.)	(2) 6 x 2
Rear Wheel Material	Poly on Poly
Rear Wheel Type	Rigid
Front Caster Qty./Diameter (in.)	(2) 2
Front Caster Material	Semi Steel
Front Caster Type	Rigid
Handle Caster Qty./Diameter/Width (in.)	(2) 4 x 1-1/4
Handle Caster Material	Poly on Poly
Handle Caster Type	Rigid

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=263>