

Steel Lift Master Boom 24 In. Fixed 15 Degrees 4,000 Lb. Capacity Blue and Yellow

MODEL LM-F15-4-24

Fork Truck Attachments / Lift Master Fork Truck Booms

PRODUCT OVERVIEW

The lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

CORE PRODUCT DATA

ASSEMBLED WEIGHT
372 lbs

ASSEMBLED SIZE
33" W x 87" L x 32" H

SHIP WEIGHT
376 lbs

PACKAGE 1 SIZE
32" W x 87" D x 33" H

COLOR / FINISH
Blue (Base Frame)/Yellow (Extension)

FREIGHT TYPE
LTL Loose

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Fork Pocket Center (in.)	24
Fork Pocket Width/Height (in.)	7-1/2 x 2-1/2
Restraint Length (in.)	36
Boom Style	Telescoping
Minimum/Maximum Hook Point (in.)	36/144
Single-Hook Capacity at 36" (lb.)	4000
Single-Hook Capacity at 48" (lb.)	3750
Single-Hook Capacity at 60" (lb.)	3500
Single-Hook Capacity at 72" (lb.)	3250
Single-Hook Capacity at 84" (lb.)	3000
Single-Hook Capacity at 96" (lbs.)	2750
Single-Hook Capacity at 108" (lbs.)	2500
Single-Hook Capacity at 120" (lbs.)	2250
Single-Hook Capacity at 132" (lbs.)	2000
Single-Hook Capacity at 144" (lbs.)	1750
Overall Extended Height (in.)	48-1/2
Retracted Hook Height (in.)	12-13/16
Extended Hook Height (in.)	28-11/32
Overall Extended Length (in.)	147
Retracted Height (in.)	33
Retracted Length (in.)	87
Overall Width (in.)	33
Retracted center of Gravity (in.)	34-7/8
Extended Center of Gravity (in.)	50-7/8
Horizontal Center of Gravity (in.)	16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=473>