# Steel Low Profile Post Table 24 In. x 36 In. 2000 Lb. Capacity Blue

**MODEL MT-2436-LP**

Ergonomic Solutions / Mechanical Post Tables



## PRODUCT OVERVIEW

The mechanical post table is an adjustable portable table that is well suited for a wide variety of material handling applications. It moves smoothly on two rigid and two swivel poly-on-steel casters. Includes bolted on adjustable floor lock. Provides positive height adjustment without a downward shift. It features a two-speed manual gear mechanism to move heavy loads.

## KEY FEATURES

- Mechanical screw operation allows precise positioning of platform
- Manual two-speed hand crank operation makes lifting and lowering quick and easy
- Two rigid and two swivel casters with floor lock allow the unit to roll smoothly
- Provides positive height adjustment without the downward shift


## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**299 lbs** | ASSEMBLED SIZE<br>**24" W x 37.875" L x 23.9375" H** | SHIP WEIGHT<br>**334 lbs** |
| PACKAGE 1 SIZE<br>**40" W x 48" D x 30" H** | COLOR / FINISH<br>**Blue** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**ADDITIONAL PRODUCT VIEWS**



## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 2,000 |
| **Platform Width (in.)** | 24 |
| **Platform Length (in.)** | 36 |
| **Lowered Height (in.)** | 23-15/16 |
| **Raised Height (in.)** | 42-3/16 |
| **Operation** | Manual |
| **Deck Thickness (in.)** | 1/4 |
| **Lift per Rotation with Heavy Load (in.)** | 1/8 |
| **Lift per Rotation with Light Load (in.)** | 5/16 |
| **Caster Quantity/Type** | (2) Rigid (2) Swivel |
| **Caster Diameter/Width (in.)** | 5 x 2 |
| **Caster Material** | Poly-on-Steel |
| **Floor Lock?** | Yes |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=282