Steel Quick Lift DC Powered 72 In. Raised Height 125 Lb. Capacity

MODEL PEL-100S-D3

Ergonomic Solutions / Powered Quick Lifts



PRODUCT OVERVIEW

The DC powered quick lift is a quiet, lightweight unit used for transport and positioning loads quickly with just the push of the button. The unit is battery operated with a high density polyethylene platform. It features a low profile design for maneuvering in narrow aisles and confined spaces. The poly casters consist of two swivel and two swivel-locking that are standard. The DC system runs with an AC on-board charger.

KEY FEATURES

- DC powered battery is fast and quite
- White HDPE platform offers durability and aesthetics
- Chain driven platform operation provides precise positioning
- Touch-pad control allows for easy operation

CORE PRODUCT DATA

ASSEMBLED WEIGHT **179 lbs**	ASSEMBLED SIZE **23.5" W x 37.5625" L x 80.3125" H**	SHIP WEIGHT **245 lbs**
PACKAGE 1 SIZE **40" W x 48" D x 88" H**	COLOR / FINISH **Blue**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS






PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	125
Lowered Height (in.)	5-5/8
Raised Height (in.)	72
Caster Diameter (in.)	3
Caster Type	(2) Swivel (2) Swivel with Brake
Caster Material	Poly-on-Poly
DC Voltage	24
AC Charger Voltage	115
Horizontal Load Center (in.)	9
Platform Width (in.)	23-1/2
Platform Length (in.)	18-1/2
Platform Thickness (in.)	1/2
Lift Speed - Loaded	26" / sec
Lift Speed - Unloaded	16" / sec
Battery Depth	6
Battery Width	8
Battery Height	4
Battery Weight	20
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=260