

Molded Rubber Serrated Bottom Wheel Chock 8 In. x 10-3/4 In. x 6 In. Black

MODEL RWC-8-SBS

Loading Dock Equipment / Rubber Wheel Chocks

PRODUCT OVERVIEW

The rubber wheel chocks are constructed of reinforced rubber to provide a sure grip on virtually any surface. The curved surface contours to fit tires. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design is durable in all weather conditions.

KEY FEATURES

- Reinforced rubber resists tearing, abrasion and ozone weathering
- Functional design is durable in all weather conditions
- Rubber provides a sure grip on virtually any surface
- Curved surface contours to fit any tire style



CORE PRODUCT DATA

ASSEMBLED WEIGHT
10 lbs

ASSEMBLED SIZE
6" W x 8" L x 10.75" H

SHIP WEIGHT
11 lbs

PACKAGE 1 SIZE
8" W x 10" D x 6" H

COLOR / FINISH
Black

FREIGHT TYPE
Parcel

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Wheel Chock Connection	None
Wheel Chock Usage	Multi-Purpose
Built-In Handles / Poles	No
Grip Surface Material	Rubber
Overall Chock Width (in.)	8
Wheel Chock Quantity	1
Bottom Style	Serrated
Overall Chock Length (in.)	10-3/4
Overall Chock Height (in.)	6

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=79>