

Steel Adjustable Stacker with Power Traction Drive System 137 In. Raised Height 2,000 Lb. Capacity Black / Yellow

MODEL SL-137-AA-PTDS

Ergonomic Solutions / Stacker with Powered Lift



PRODUCT OVERVIEW

Semi-electric Stackers with powered lift will raise and lower loads quickly and easily. All models are easily maneuverable using the standard pulling handle. Stackers are highly efficient and durable. Powered traction drive system allows the user to transfer the unit and materials easily across an array of surfaces.

KEY FEATURES

- Powered fork height adjustment provides user friendly adjustment
- Pivoting steering handle allows for easy pushing or pulling
- Battery level gauge allows operator to monitor battery life
- Steel construction offers highly efficient and durable use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1295 lbs

ASSEMBLED SIZE
88.5625" W x 66.125" L x 58" H

SHIP WEIGHT
1378 lbs

PACKAGE 1 SIZE
64" W x 75" D x 94" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity at 0 - 62" (lb.)	2,000
Uniform Capacity at 62 - 118" (lb.)	1,500
Uniform Capacity at 118 - 137" (lb.)	1,000
Service Range (in.)	2 to 137
Fork Width/Length (in.)	4 x 42
Adjustable Fork Spacing (in.)	8 to 26-3/4
Adjustable Leg Spacing (in.)	40-1/8 to 50
Drive Motor	DC 24V / 0.4 KW
Phase	Single Phase
Battery	(2) 12V / 95 Ah
Charger	DC 24V / 6 amp
Number of Casters / Wheels	4
Rear Caster Diameter/Width (in)	7 x 2-1/2
Front Caster Diameter/Width (in)	4 x 2-9/10
Caster Material	Nylon
Power Source	Electric - Corded
Travel Speed w/ Load (MPH)	1.5
Travel Speed w/o Load (MPH)	2.2
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=250>