Steel Narrow Mast Stacker DC Powered 90 In. Raised Height Adjustable Forks and Support Legs 2,500 Lb. Capacity Black / Yellow

MODEL SNM-90-AA

Ergonomic Solutions / Narrow Mast Stackers with Powered Drive and Powered Lift



PRODUCT OVERVIEW

The narrow mast stacker is great for the shipping and manufacturing facilities. The stacker provides a fast efficient solution to loading and unloading products in closely confined areas. The stacker features a simple throttle design for lifting control, as well as, infinite forward and reverse speed adjustments. The unit drives on poly on steel steering and load wheels, which provide excellent maneuverability. A battery charger, gauge and horn are included. Models are available with fixed or adjustable forks as well as fixed or adjustable leg supports.

KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Stacker is an efficient solution to loading and unloading in closely confined areas
- Throttle design lifts and controls speed adjustments for ideal operation and optimal results
- Includes poly-on-steel wheels for excellent maneuverability and adjustable forks for maximum efficiency

CORE PRODUCT DATA

ASSEMBLED WEIGHT **1272 lbs**	ASSEMBLED SIZE **58" W x 68.5" L x 64" H**	SHIP WEIGHT **1350 lbs**
PACKAGE 1 SIZE **65" W x 80" D x 72" H**	COLOR / FINISH **Black / Yellow**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS






PRODUCT SPECIFICATIONS

Uniform Capacity at 0 - 62" (lb.)	2,500
Uniform Capacity at 62 - 90" (lb.)	2,000
Service Range (in.)	2-1/8 to 90-1/2
Fork Width/Length (in.)	4 x 42-1/8
Adjustable Fork Spacing (in.)	8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	40-1/8 to 50 (ID)
Overall Mast Height - Retracted (in.)	63-3/4
Overall Mast Height - Extended (in.)	108-1/4
Drive Motor	DC 24V / 1.0 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 70-80 Ah
Battery Charger	24V / 12 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Travel Speed - Loaded (MPH)	3.1
Travel Speed - Unloaded (MPH)	3.8
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=251