

Steel Trailer Stabilizing Spin Top Beam Jack 26-11/16 In. x 23-3/4 In. x 40 In. 100,000 Lb. Static Capacity Yellow

MODEL SP-TOP-BEAM

Loading Dock Equipment / Trailer Stabilizing Jacks



PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish is included. **The color of handles included with models may vary between red and black**.

KEY FEATURES

- Meets OSHA regulations when used with wheel chocks
- Manual raising and lowering mechanism
- Rectangle top plate
- Reflective collar for great visibility at night

CORE PRODUCT DATA

ASSEMBLED WEIGHT
147 lbs

ASSEMBLED SIZE
40" W x 26.6875" L x 23.75" H

SHIP WEIGHT
200 lbs

PACKAGE 1 SIZE
40" W x 48" D x 45" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Static Capacity (lb.)	100,000
Uniform Lifting Capacity (lb.)	40,000
Lowered Height (in.)	40
Raised Height (in.)	51
Wheel Quantity/Diameter/Width (in.)	(2) 10 x 2
Wheel Type	Hard Rubber
Front Wheel Quantity/Diameter/Width (in.)	(1) 4 x 1-1/2
Front Wheel Type	Steel

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=90>