

Steel Dock Safety Swing Gate 10 Ft. Length Gray Semi Gloss

MODEL SSG-10-GYSG

Loading Dock Equipment / Economical Safety Swing Gates

PRODUCT OVERVIEW

Economical safety swing gates are an economical way to protect people from dock falls. Durable railings are constructed from schedule 10 pipe (1-5/8" O.D.). Units have a top rail height of 46-1/4" and a 25" mid-rail. 4" poly-on-poly wheel allows units to be swung out of the way. Cast single socket is included.

KEY FEATURES

- Ideal for loading docks, floor openings, and mezzanines
- Pre-drilled base plate mounting holes
- Gray powder coat finish
- Foot release lock keeps railing from moving when in use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
62.83 lbs

ASSEMBLED SIZE
46.25" W x 120.0625" L x 6.5" H

SHIP WEIGHT
154 lbs

PACKAGE 1 SIZE
48" W x 127" D x 12" H

COLOR / FINISH
Gray Semi Gloss

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

PRODUCT SPECIFICATIONS

Wheel Quantity/Diameter/Width (in.)	(1) 4 x 1-1/4
Wheel Material	Poly-on-Poly
Steel Pipe (Schedule)	10
Pipe O.D. (in.)	1-5/8
Midrail (in.)	25
Weight (lbs.)	84

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=11>