

Steel Semi-Automatic Stretch Wrap Machine 50 In. Turntable Diameter 4,000 Lb. Capacity Blue / Yellow

MODEL SWA-50

Packaging Equipment / Powered Stretch Wrap Machines

PRODUCT OVERVIEW

The semi-automatic stretch wrap machine design offers bigger carousel sizes with carousel rotation that is controlled by a foot switch. The power input has variable AC motor that allows adjustable deck speed and includes soft-start/stop. The film-wrap tension is controlled with an adjustable, friction-brake assembly. Film placement is controlled manually by moving the carriage assembly up and down on the vertical mast. An easy-to-release, hand operated carriage-brake allows the carriage to move freely making film application fast and simple. The system will accept 10 (in.) to 20 (in.) material. The unit ships with mast disconnected—simply raise mast and clamp into place.

KEY FEATURES

- Stretch wrap design increases shipping productivity
- Simple depress foot pedal powers turntable
- Manual mast allows user to wrap the needed areas
- Steel construction provides a long lasting rugged use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
544 lbs

ASSEMBLED SIZE
92.375" W x 87.125" L x 50" H

SHIP WEIGHT
615 lbs

PACKAGE 1 SIZE
64" W x 96" D x 26" H

COLOR / FINISH
Yellow (Deck), Blue (Frame)

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Turntable Diameter (in.)	50
Wrap Height (in.)	82
Turntable Height (in.)	2-1/16
Maximum Load Diameter (in.)	64
Voltage/Phase	115/1
Motor Amperage	1.8
R.P.M Variables	3-12
Motor Horsepower	1/2
Foot Switch Cord Length (in.)	96
Minimum Compatible Stretch Wrap Core ID (in.)	3
Maximum Compatible Stretch Wrap OD (in.)	11

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=367>