

Steel Winch Truck Jib Crane 500 Lb. Extended Capacity Yellow

MODEL WTJ-2

Overhead Lifting / Winch Operated Truck Jib Cranes

PRODUCT OVERVIEW

Installed in your pick-up truck bed, this winch operated truck Jib crane will help lift loads. Lift items from ground to truck bed height, then rotates into cargo area. Includes telescopic boom design with manual hydraulic hand pump to pivot boom up and down. Manual cable winch to lift and lower loads. Unit comes with one grab hook, one chain slot lock, and one sling hook with latch. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

KEY FEATURES

- Mounts to truck bed allowing for easy product loading and unloading
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
115 lbs

ASSEMBLED SIZE
33" W x 10.625" L x 56.75" H

SHIP WEIGHT
135 lbs

PACKAGE 1 SIZE
12" W x 65" D x 17" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Cable Winch Capacity (lb.)	500
Extended Fixed Hook Capacity (lb.)	500
Extended Usable Reach (in.)	54
Extended Maximum Hook Height (in.)	102
Extended Minimum Hook Height (in.)	Zero
Retracted Fixed Hook Capacity (lb.)	1,000
Retracted Usable Reach (in.)	30-1/4
Retracted Maximum Hook Height (in.)	89-1/2
Retracted Minimum Hook Height (in.)	10
Overall Cable Length (ft.)	14-1/2
Usable Cable Length (ft.)	9
Cable Diameter (in.)	3/16
Mounting Plate Length (in.)	10-5/8
Mounting Plate Width (in.)	10-5/8
Base Height (in.)	11-3/4
Rotation (degrees)	360
Piston Stroke (in.)	16-3/8
Piston Stroke Per Pump (in.)	1/16
Cable Retracts/Extension Per Crank (in.)	1-1/2
Number of Cranks to Retract/Extend Cable	72
Wire Rope Material	Galvanized Steel
Hook Material	Steel
Hook Opening (in.)	1-3/32
Hook Movement	Rigid
Fasteners Included	No
Mounting Hole Diameter (in.)	11/16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=578>