

# Galvanized Steel AC Powered Jib Crane CSA Compliant 4-7 Ft. Boom 2,000 Lb. Capacity Gray

**MODEL WTJ-20-4-AC-CSA-GAL**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

The power lift Jib cranes are designed for material handling applications on docks, in warehouses or in truck beds. Choose either 12V DC, 1 HP with 6-foot long removable pendant control or 115V AC 1/3 HP with fingertip switch to raise and lower hook. Meets ANSI and OSHA specifications. 12" x 12" mounting plate. Units are not rated for overhead lifting applications. Consult factory for pricing if overhead lifting rating is required. Intermittent use cranes feature rotation hand brakes that offer unlimited 360 degrees positioning. Mast mounts permanently. Boom adjusts in 12" increments and can be positioned at 4 elevations. The AC units feature 25 feet of 7/32" cable. Folds for storage.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**236 lbs**

ASSEMBLED SIZE  
**73" W x 87.5" L x 18.6875" H**

SHIP WEIGHT  
**281 lbs**

PACKAGE 1 SIZE  
**29" W x 66" D x 17" H**

COLOR / FINISH  
**Gray**

FREIGHT TYPE  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                             |                   |
|---------------------------------------------|-------------------|
| Uniform Capacity (lb.)                      | 2000              |
| Boom Reach (in.)                            | 51-1/4 to 87-1/4  |
| Boom Height (in.)                           | 59-1/2 to 106-1/2 |
| Rotation Degree                             | 360               |
| Boom Adjustment Increments (in.)            | 12                |
| Cable Length (ft.)                          | 25                |
| Cable Diameter (in.)                        | 7/32              |
| AC (volts)                                  | 120               |
| Horsepower (HP)                             | 1/3               |
| Mounting Plate Length (in.)                 | 12                |
| Mounting Plate Width (in.)                  | 12                |
| Capacity at 59-1/2" Fully Retracted (lbs.)  | 1,100             |
| Capacity at 59-1/2" Second Position (lbs.)  | 800               |
| Capacity at 59-1/2" Third Position (lbs.)   | 600               |
| Capacity at 59-1/2" Fully Extended (lbs.)   | 250               |
| Capacity at 78-1/4" Fully Retracted (lbs.)  | 1,500             |
| Capacity at 78-1/4" Second Position (lbs.)  | 1,200             |
| Capacity at 78-1/4" Third Position (lbs.)   | 1,000             |
| Capacity at 78-1/4" Fully Extended (lbs.)   | 600               |
| Capacity at 94-1/2" Fully Retracted (lbs.)  | 1,850             |
| Capacity at 94-1/2" Second Position (lbs.)  | 1,450             |
| Capacity at 94-1/2" Third Position (lbs.)   | 1,250             |
| Capacity at 94-1/2" Fully Extended (lbs.)   | 780               |
| Capacity at 106-1/2" Fully Retracted (lbs.) | 2,000             |
| Capacity at 106-1/2" Second Position (lbs.) | 2,000             |
| Capacity at 106-1/2" Third Position (lbs.)  | 1,900             |
| Capacity at 106-1/2" Fully Extended (lbs.)  | 1,200             |
| Compliant                                   | CSA               |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>